



RAL11
Unit for conductive electrodes

Level control with conductivity electrodes
Suitable for conductive liquids measurement (21microS ÷ 2100microS)
24/115/230Vac power supply
Connections with UNDECAL socket



RAL12
Unit for conductive electrodes

Level control with conductivity electrodes
Suitable for conductive liquids measurement (21microS ÷ 2100microS)
24/115/230Vac power supply
Connections with UNDECAL socket



RAL13
Unit for conductive electrodes

Level control with conductivity electrodes
Suitable for conductive liquids measurement (4microS ÷ 1000microS)
24/115/230Vac; 24 Vdc power supply
Delay time adjustable
Connections with UNDECAL socket



RAL11 Unit for level conductive electrodes
 Min/max conductive level control or pump control
 Alternate control voltage to the electrodes
 2 relays SPDT contacts 3A/250Vac - Adj.sensibility
 Undecal plug-in male-socket; IP40 frontal
 Working temperature -20 +50°C

Version	
A	Standard
B	IP56 (inside plastic housing cod 545A015N)
Z	Special
Power supply	
0	24Vac 50+60Hz
1	115Vac 50+60Hz
2	230Vac 50+60Hz
Accessories	
A	None
B	Undecal socket + fixing spring
Z	Special

RAL12 Unit for level conductive electrodes
 Min/max conductive level control; adj.sensibility
 Alternate control voltage to the electrodes
 Control of the electrodes electrical connection "security relay"
 N1 level control relay; SPDT contacts 3A/250Vac
 N1 safety relay; SPDT contacts 3A/250Vac
 Undecal plug-in male-socket; IP40 frontal
 Working temperature -20 +50°C

Version	
A	Standard
B	IP56 (inside plastic housing cod 545A015N)
Z	Special
Power supply	
0	24Vac 50+60Hz
1	115Vac 50+60Hz
2	230Vac 50+60Hz
Accessories	
A	None
B	Undecal socket + fixing spring
Z	Special

RAL13 Unit for level conductive electrodes
 Min/max conductive level control or pump control
 Alternate control voltage to the electrodes
 2 relays SPDT contacts 3A/250Vac
 Adj. sensibility and delay time
 Undecal plug-in male-socket; IP40 frontal
 Working temperature -20 +50°C

Version	
A	Standard
B	IP56 (inside plastic housing cod 545A015N)
Z	Special
Power supply	
0	24Vac 50+60Hz
1	115Vac 50+60Hz
2	230Vac 50+60Hz
4	24Vdc
Accessories	
A	None
B	Undecal socket + fixing spring
Z	Special