



RL6
Conductive level switch

Multi-electrode rod probe
IP66
Up to 5 rods
Max electrode length 3 meters



RL8
Conductive level switch

Multi-electrode rod probe
IP66
Up to 5 rods
Max electrode length 30 meters



RL6 Multi rods electrode
 Conductive level control; max 5 rods
 Max electrode length: 3m

Housing	
B	Polycarbonate loaded; IP66
E	DIN B aluminum painted (n.1 electrode selection available); IP66
G	DIN A aluminum painted; IP66
Z	Special
Process connection	
02	G 1" / SS316, max 4 electrodes Ø5mm - not for DIN B housing
04	1" NPT-M / SS316 - max 4 electrodes Ø5mm - not for DIN B housing
05	G 1" / PVC - max 4 electrodes Ø5mm - not for DIN B housing
12	G 1" ½ / SS316 - not for DIN B housing
18	G 1" ½ / PVC - not for DIN B housing
20	DN25 DIN11851 SS304L (sanitary) - only with B housing and 1 electrode
21	DN40 DIN11851 SS304L (sanitary) - only with B housing
22	DN50 DIN11851 SS304L (sanitary) - only with B housing
71	Clamp 1" SS316 - not for DIN B housing
73	Clamp 1" ½ SS316 - not for DIN B housing
75	Clamp 2" material SS316 - only for B housing
84	G ½" / SS316 - only with DIN B housing and 1 electrode (option B)
85	½" NPT-M / SS316 - only with DIN B housing and 1 electrode (option B)
92	G ¾" / SS316 - only with DIN B housing and 1 electrode Ø10mm (option B)
93	¾" NPT-M / SS316 - only with DIN B housing and 1 electrode Ø10mm (option B)
99	Special
Nr. of electrodes	
B	1
C	2; only for process fitting cod. 02, 04, 05, 12, 18, 20, 21, 22, 71, 73, 75, 94
D	3; only for process fitting cod. 02, 04, 05, 12, 18, 21, 22, 71, 73, 75
E	4; only for process fitting cod. 02, 04, 05, 12, 18, 21, 22, 71, 73, 75
F	5; only for process fitting cod. 12, 18, 21, 22, 75
Z	Special
Electrodes type, insulation and length - price per 100mm of each electrode (max 3m)	
36	Ø5mm SS316 rod
37	PVC coated Ø5mm SS316 rod
38	PTFE coated Ø5mm SS316 rod
40	Ø10mm SS316 rod, only for one electrode
41	PVC coated Ø10mm SS316 rod, only for one electrode
44	PTFE coated Ø10mm SS316 rod, only for one electrode
99	Special

RL8 Multi ropes electrode
 Conductive level control; max. 5 ropes
 Max electrodes length 30m

Housing	
B	Polycarbonate loaded; IP66
Z	Special
Process connection	
02	G 1" / SS316
04	1" NPT-M / SS316
05	G 1" / PVC
12	G 1" ½ / SS316
18	G 1" ½ / PVC
19	G 1" ½ / PTFE
71	Clamp 1" / SS316
73	Clamp 1" ½ / SS316
75	Camp 2" / SS316
99	Special
Nr. of electrodes	
B	n.1
C	n.2
D	n.3
E	n.4; only for connection cod. 12, 18, 73, 75
H	n.5; only for connection cod. 12, 18, 73, 75
Z	Special
Rope type, price per meter of each electrode	
81	PVC insulated Ø1,5mm SS316
99	Special